



IT TECHCOM CO., LTD.  
123/765 Moo 11 Navamin Road, Kannayao, Kannayao, Bangkok 10230  
Tel: (662) 948-6990 (Auto 12 numbers) ; Fax: (662) 948-6900



The VIVOTEK IP7132, incorporating our self-developed VVTK-1000 SoC processor, offers superior quality MPEG-4 videos at 30 fps in full VGA resolution, and gives viewers image clarity and transmission efficiency that was once

impossible. It comes with 3GPP/ISMA compatibility; a new ability allowing users to monitor cameras from not only standard web browser or application software, but also 3G cellular phones anytime, anywhere. IP7132 supports a wireless connection for attachment to any existing 802.11g wireless LAN. More features are enhanced in IP7132 to meet specific, versatile applications such as digital I/O interface, and appropriate lens selection with CS-mount. The VIVOTEK IP7132 allows users to easily build up a surveillance system for their exclusive, various needs.

- VGA CMOS Sensor
- Up to 30 fps in Full VGA Resolution
- Real-time MPEG-4 Compression (Simple Profile)
- 802.11g Wireless Connection
- Supports 3GPP/ISMA Mobile Surveillance
- Digital I/O for Sensor and Alarm
- Easy to Install and Configure
- Optimized Synchronization of Audio and Video
- Video Motion Detection, with Pre- and Post- Alarm Snapshots
- Superior Low Light Performance

#### Product Rear View



Quick Guide

Warranty Card