



IT TECHCOM CO., LTD.
123/765 Moo 11 Navamin Road, Kannaayo, Kannaayo, Bangkok 10230
Tel: (662) 948-6990 (Auto 12 numbers) ; Fax: (662) 948-6900



The VIVOTEK IP7139 is a professional network camera with mega-pixel resolution for indoor surveillance applications and detail remote monitoring. Equipped with a 1.3 Mega-pixel (1280x1024) CMOS sensor delivering superior image details, it could be the best choice for

monitoring extensive areas such as airports, factories, retail stores, schools, offices or banks. Embedded with VIVOTEK VVTK-1000 SoC, it enables to deliver dual streams with different resolutions and video quality upon different devices simultaneously such as PC (MPEG-4 or MJPEG), or 3G cell phone (MPEG-4 only). In addition, the VIVOTEK IP7139 builds in a compact flash card slot for local storage in case of connection failure. It also supports 3GPP mobile surveillance, which enables users to monitor via 3G cell phones or any RTSP (Real Time Streaming Protocol) compatible multimedia device on the go. More features are enhanced in the VIVOTEK IP7139 to meet specific applications such as two-way audio, digital I/O interface, 802.11 b/g WLAN, and appropriate lens selection with CS mount. With its versatile functions, the VIVOTEK IP7139 provides a total solution for customers' diverse needs.

- Mega-pixel CMOS Sensor
- Appropriate Lens Selection with CS Mount
- Built-in CF Card Slot for Local Storage
- MPEG-4 and MJPEG Video Compression (Dual Codec)
- Supports Simultaneous Dual Streams (RTSP Streaming for MPEG-4 Mode with Resolution up to 800x600; Server Push for MJPEG Mode with Resolution up to 1280x1024)
- Supports 3GPP Mobile Surveillance
- Supports Two-way Audio (*)
- Built-in 802.11b/g WLAN
- One D/I and One D/O for Sensor and Alarm
- Supports Privacy Masks

The features with (*) will be available later through firmware upgrade.

Product Rear View





Quick Guide



Warranty Card